

Product Data Sheet

Edition: 6/2009

Version no: 0006

Sarnacol 2121 Adhesive

Overview:	Sarnacol 2121 is a water-based dispersion adhesive used within a Sika Sarnafil Adhered system. It is formulated for adhering PVC membranes to clean and dry, water absorbent, horizontal surfaces only with slopes up to 10° (2/12).
Composition:	See Material Safety Data Sheet for information. VOC Content: 120.4 g/L
Features:	Sarnacol 2121 is uniquely formulated to be compatible with Sarnafil membranes. Sarnacol 2121 has a shelf life of 12 months in a tightly closed container in temperatures between 32 and 99 degrees F (0 and 37 degrees C).
Packaging:	Sarnacol 2121 is supplied in 5-gallon plastic containers weighing 45 lbs (20.4 kg).
Installation:	Sarnacol 2121 is applied with a notched-squeegee to the substrate only, the membrane is rolled onto the adhesive while it is still wet and rolled firmly into place with a water-filled, foam-covered lawn roller. There is no adhesive drying time resulting in faster membrane application. Precautionary measures must be taken to avoid exposing Sarnacol 2121 to low temperatures. Sarnacol 2121 may only be used and stored in temperatures greater than 40 °F (5°C). In cool or humid weather the Sarnacol 2121 will take longer to cure. Sarnacol 2121 is not to be used on vertical or sloped surfaces greater than a 2 inch (50 mm) rise per 1 horizontal foot (0.3 m).
Availability:	Sarnacol 2121 is available directly from Sika Sarnafil Authorized Applicators when used within a Sika Sarnafil Roofing or Waterproofing System. Contact your Sika Sarnafil Regional Office or visit our website for further information.
Warranty:	As a Sika Sarnafil-supplied accessory, Sarnacol 2121 is included in Sika Sarnafil's Standard or System Warranty to the Building Owner.

The Sarnafil logo consists of the word "Sarnafil" in a bold, blue, sans-serif font, followed by a registered trademark symbol (®).

Maintenance:	Sarnacol 2121 requires no maintenance.	
Technical:	Sika Sarnafil provides technical support. Technical staff is available to advise Applicators as to the correct installation method of Sarnacol 2121.	
Technical Data:	<u>Substrate</u>	<u>Total Rate</u>
	Isocyanurate Facer	1-½ gallons per square (0.61 liters/meter ²)
	Smooth Plywood	1-½ gallons per square (0.61 liters/meter ²)
	Georgia Pacific Dens-Deck Prime®	1-¼ gallons per square (0.51 liters/meter ²)
	<u>Substrate</u>	<u>Total Rate for Feltback Membrane</u>
	Isocyanurate Face	1-¾ gallons per square (0.71 liters/meter ²)
	Smooth Plywood	1-¾ gallons per square (0.71 liters/meter ²)
	Concrete Deck	2 gallons per square (0.81 liters/meter ²)
	Cellular Concrete (feltback membrane only)	2 gallons per square (0.81 liters/meter ²)
	Georgia Pacific Dens-Deck®	1-¾ gallons per square (0.71 liters/meter ²)
	Georgia Pacific Dens-Deck Prime®	1-½ gallons per square (0.61 liters/meter ²)

Corporate Office
Sika Sarnafil
A Division of Sika Corporation
100 Dan Road
Canton, MA 02021

Tel.: (781) 828-5400
1-800-451-2504

Fax: (781) 828-5365

Web: www.sikacorp.com

Email: webmaster.sarnafil@us.sika.com

Canada Office
Sika Sarnafil
A Business Unit of Sika Canada
6820 Davand Drive
Mississauga, ON L5T 1J5

Tel.: (905) 670-2222
1-800-268-0479

Fax: (905) 670-5278

Web: www.sika.ca

Disclaimer: The information, and, in particular, the recommendation relating to the application and end-use of Sika Sarnafil products, are given in good faith based on Sika Sarnafil's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika Sarnafil recommendations. In practice, the differences in materials, substrates and actual site conditions are such that **no warranty in respect of merchantability of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, may be inferred from this information.** The user of the product must determine the product's suitability for the intended application and purpose. Sika Sarnafil reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.