

# Polymer Fastener Insulation Plate

Firestone Item Number: W56RAC4503

### **DESCRIPTION:**

Polymer Fastener Insulation Plates are specifically designed to be used with the Firestone Polymer Fastener in roofing applications for attaching insulation as specified in current Firestone Specifications and Details.

#### **METHOD OF APPLICATION:**


Position plates over roof insulation as specified by the Firestone Specifications and Details. Attach plates to roof deck using the appropriate length Firestone Polymer Fastener. Install plates showing "THIS SIDE UP".

Contact your Firestone Technical Coordinator at 1-800-428-4511 for specific application information

## **PRECAUTIONARY DATA:**

- Do not overdrive or underdrive fastener.
- Plates are designed to anchor roof insulation only.
- Avoid field seams directly over insulation plates.

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



## PRODUCT DATA

# Property Minimum Performance

Material: Galvalume®, AZ55
Material Thickness: 0.017" (.43 mm) - 0.023"

(0.58 mm)

Corrosion Resistance: Meets FM No. 4470 criteria Pull-Through Resistance: 400 lb (181.4 kg) (min.) from

center hole

Diameter: 3" (75.2 mm)

Galvalume® is a registered trademark of BIEC International Inc.

#### STORAGE:

Store in original unopened containers protected from the weather.

# **PACKAGING:**

Pail: 500 plates Weight: 31 lb (14 kg)/pail

Pallet: 72 pails

### **LEED INFORMATION:**

Post Consumer Recycled Content: 0% Post Industrial Recycled Content: 0%

Manufacturing Location: New Rochelle, NY



#### **Firestone Building Products Company**

250 W. 96<sup>th</sup> Street, Indianapolis, IN 46260 Sales: (800) 428-4442 • Technical (800) 428-4511 www.firestonebpco.com